

Meet Cody!

The New Label Printer by GA International

NEW!



The GA Cody-3™ Thermal Printer

The Cody-3 desktop thermal printer is capable of printing high-quality 300 dpi text, barcodes, and graphics on many label types and configurations. It can print directly on thermal media or in thermal-transfer mode using an ink ribbon. Professional looking labels can be achieved by following the easy-to-use software (trial included). Multiple connectivity options are also included.

Simple, Robust, & Affordable

- Accepts label rolls up to 4.64" wide
- Barcoding software trial for designing labels
- 300 dpi print resolution, for small label printing
- Direct thermal or thermal-transfer modes available
- USB, serial, parallel, and ethernet interface options



What's in the Box

- › Cody-3 printer
- › Power cord*
- › Power adapter
- › USB cable
- › Cardboard take-up core
- › Ribbon holder and take-up spools
- › Flash drive with BarTender software (trial version) and printer driver installation instructions

*The product includes a North American, European, or UK power cord and adapter. Other country-specific power cords must be purchased locally and separately.



Technical Specifications

- › **Print Method:** Thermal-Transfer/Direct Thermal
- › **Print Resolution:** 300 dpi
- › **Interfaces:** USB, Serial, Ethernet
- › **Print Speed:** up to 4" (102mm/s)
- › **Max. Print Width:** 4.16" (105.7mm)
- › **Max. Print Length:** 30" (762mm)
- › **Label Width:** 1" to 4.64" (25.4 to 118mm)
- › **Label Height:** 0.157"-30" (4-762mm)
- › **Media Types:** Continuous, Die-cut/gap Labels (Black Marked, Notch), Fanfold
- › **Media Width:** 1" to 4.64" (25.4 to 118mm)
- › **Media Roll Core Size:** 1"
- › **Media Maximum Roll OD:** 5" (127mm)
- › **Ribbon Maximum OD:** 2.67" (68mm)
- › **Ribbon Maximum Length:** 984' (300m)
- › **Ribbon Core Size:** 1" (25.4mm)
- › **Ribbon Width:** Min. 1.18" (30mm), Max. 4.3" (110mm)
- › **Ribbon Winding:** Ink Side Out (ISO)

Shop on www.industritag.com/cody-3